






	MobileOffice D430	MobileOffice D600 Plus	MobileOffice D600	MobileOffice D620	MobileOffice S602
Product Picture					
Image Sensor	CIS x 2	CIS x 2	CIS x 2	CIS x 2	CIS
Optical Resolution	600 dpi	600 dpi	600 dpi	600 dpi	1200 dpi
Scan Modes	Color: 48-bit Input; 24-bit Output Grayscale: 16-bit Input; 8-bit Output B/W: 1-bit	Color: 48-bit Input; 24-bit Output Grayscale: 16-bit Input; 8-bit Output B/W: 1-bit	Color: 48-bit Input; 24-bit Output Grayscale: 16-bit Input; 8-bit Output B/W: 1-bit	Color: 48-bit Input; 24-bit Output Grayscale: 16-bit Input; 8-bit Output B/W: 1-bit	Color: 48-bit Input; 24-bit Output Grayscale: 16-bit Input; 8-bit Output B/W: 1-bit
Scanning Speed	Simplex: 1.8 sec (Grayscale Mode, 200 dpi, A4) Duplex: 2.4 sec (Grayscale Mode, 200 dpi, A4)	Simplex: 2.2 sec (Grayscale Mode, 300 dpi, A6) Duplex: 2.5 sec (Grayscale Mode, 300 dpi, A6)	Simplex: 1.3 sec (Grayscale Mode, 300 dpi, A6) Duplex: 1.7 sec (Grayscale Mode, 300 dpi, A6)	Simplex: 1.8 sec (Grayscale Mode, 200 dpi, A4) Duplex: 2.4 sec (Grayscale Mode, 200 dpi, A4)	5.5 sec (Color Mode, 300 dpi, A6)
Scanning Area (W x L)	Max.: 216 x 1270 mm (8.5" x 50") Min.: 12.7 x 12.7 mm (0.5" x 0.5")	Max: 101.6 x 593.3 mm (4" x 23.36") Min: 40 x 45 mm (1.57" x 1.77")	Max: 101.6 x 593.3 mm (4" x 23.36") Min: 12.7 x 12.7 mm (0.5" x 0.5")	Max.: 216 x 1270 mm (8.5" x 50") Min.: 12.7 x 12.7 mm (0.5" x 0.5")	Maximum: 104.9 x 500 mm (4.13" x 19.69") Minimum: 33 x 43 mm (1.3" x 1.7") TWAIN support 104.9 x 500 mm (4.13" x 19.69")
Acceptable Paper Sizes (W x L)	Max.: 240 x 1270 mm (9.45" x 50") Min.: 30 x 35 mm (1.18" x 1.38")	Max: 107 x 593.3 mm (4.21" x 23.36") Min: 40 x 45 mm (1.57" x 1.77")	Max: 107 x 593.3 mm (4.21" x 23.36") Min: 40 x 45 mm (1.57" x 1.77")	Max.: 240 x 1270 mm (9.45" x 50") Min.: 30 x 35 mm (1.18" x 1.38")	Plastic card: Non-Embossed up to 0.76 mm
Action Button	Scan, Function x 2 (Up & Down)	Scan & Power	Scan	Scan, Function x 2 (Up & Down)	Scan, Custom
Power Supply	AC Power: 24V / 0.75A	AC Power: 24V / 0.75A	AC Power: 15 Vdc / 1 A	AC Power: 24V / 0.75A	USB Power: 5V / 0.5A
Interface	USB 2.0	USB 2.0	USB 2.0	USB 2.0	USB 2.0
Net Weight	0.96 Kgs (2.13 Lbs)	0.45 Kgs (1 Lbs)	0.45 Kgs (1 Lbs)	0.96 Kgs (2.13 Lbs)	0.19 Kgs (0.42 Lbs)
Dimensions (W x D x H)	303 x 94 x 60 mm (11.93" x 3.7" x 2.36")	194 x 75 x 55 mm (7.63" x 2.95" x 2.17")	194 x 73 x 54 mm (7.64" x 2.87" x 2.13")	303 x 94 x 60 mm (11.93" x 3.7" x 2.36")	174.5 x 60.5 x 38.5 mm (6.87" x 2.38" x 1.52")
Protocol	TWAIN compliant	TWAIN compliant	TWAIN compliant	TWAIN compliant	TWAIN compliant
OS	Windows XP / Vista / 7 / 8 / 10	Windows 7 / 8 / 10	Windows 7 / 8 / 10	Windows XP / Vista / 7 / 8 / 10	Windows 7 / 8 / 10
Hardware Requirements	Pentium® IV 2.4 GHz processor DVD-ROM Drive One available USB 2.0 Port 1GB RAM (2GB or higher recommended) 2GB free HDD space (3GB or larger recommended)	Pentium® IV 2.4 GHz processor DVD-ROM Drive One available USB 2.0 Port 1GB RAM (2GB or higher recommended) 2GB free HDD space (3GB or larger recommended)	Pentium® IV 2.4 GHz processor DVD-ROM Drive One available USB 2.0 Port 1GB RAM (2GB or higher recommended) 2GB free HDD space (3GB or larger recommended)	Pentium® IV 2.4 GHz processor DVD-ROM Drive One available USB 2.0 Port 1GB RAM (2GB or higher recommended) 2GB free HDD space (3GB or larger recommended)	Pentium® IV 2.4 GHz processor DVD-ROM Drive One available USB 2.0 Port 1GB RAM (2GB or higher recommended) 2GB free HDD space (3GB or larger recommended)