






	SecureScan X50	SecureScan X100	SecureScan X150	SecureScan X200	SecureScan X-Mini
Product Picture					
Image Sensor	CMOS	CMOS	CMOS	CMOS	CMOS
Light Source	White LED	White LED / IR LED	White LED / IR LED / UV LED	White LED / IR LED / UV LED	White LED / IR LED
Optical Resolution	5 Megapixels	5 Megapixels	5 Megapixels	5 Megapixels	5 Megapixels
Focus	Fixed	Fixed	Fixed	Fixed	Fixed
Scan Modes	Color: 24-bit Input; 24-bit Output	Color: 24-bit Input; 24-bit Output IR: 24-bit Input; 8-bit Output	Color: 24-bit Input; 24-bit Output IR: 24-bit Input; 8-bit Output UV: 24-bit Input; 24-bit Output	Color: 24-bit Input; 24-bit Output IR: 24-bit Input; 8-bit Output UV: 24-bit Input; 24-bit Output	Color: 24-bit Input; 24-bit Output IR: 24-bit Input; 8-bit Output
Scanning Speed	Approx. 1 sec (Color Mode, Full Page passport image capture)	Approx. 1 sec (Color Mode, Full Page passport image capture)	Approx. 2 sec (Color Mode, Full Page passport image capture)	Approx. 2 sec (Color Mode, Full Page passport image capture)	Approx. 1 sec (Color Mode, Full Page passport image capture)
Scanning Area (W x L)	Maximum: 127 x 95 mm (5" x 3.74")	Maximum: 127 x 95 mm (5" x 3.74")	Maximum: 127 x 95 mm (5" x 3.74")	Maximum: 127 x 95 mm (5" x 3.74")	Maximum: 127 x 95 mm (5" x 3.74")
Acceptable Paper Sizes (W x L)	Maximum: 125 x 88 mm (4.92" x 3.46")	Maximum: 125 x 88 mm (4.92" x 3.46")	Maximum: 125 x 88 mm (4.92" x 3.46")	Maximum: 125 x 88 mm (4.92" x 3.46")	Maximum: 125 x 88 mm (4.92" x 3.46")
Action Button	Dual Auto Detect Sensors	Dual Auto Detect Sensors	Dual Auto Detect Sensors	Dual Auto Detect Sensors	Dual Auto Detect Sensors
Power Supply	USB Power: 5V / 0.5A	USB Power: 5V / 0.5A	AC Power: 24V / 0.75A	AC Power: 24V / 0.75A	USB Power: 5V / 0.5A
Interface	USB 2.0	USB 2.0	USB 2.0 USB 2.0 Port x 2 (Extension)	USB 2.0 USB 2.0 Port x 2 (Extension)	USB 2.0
Net Weight	1.7 Kgs (3.78 Lbs)	1.7 Kgs (3.78 Lbs)	1.7 Kgs (3.78 Lbs)	1.7 Kgs (3.78 Lbs)	0.86 Kgs (1.91 Lbs)
Dimensions (W x D x H)	Without Cover: 200 x 200 x 119 mm (7.87" x 7.87" x 4.69") With Cover: 200 x 200 x 190 mm (7.87" x 7.87" x 7.48")	Without Cover: 200 x 200 x 119 mm (7.87" x 7.87" x 4.69") With Cover: 200 x 200 x 190 mm (7.87" x 7.87" x 7.48")	Without Cover: 200 x 200 x 119 mm (7.87" x 7.87" x 4.69") With Cover: 200 x 200 x 190 mm (7.87" x 7.87" x 7.48")	Without Cover: 200 x 200 x 119 mm (7.87" x 7.87" x 4.69") With Cover: 200 x 200 x 190 mm (7.87" x 7.87" x 7.48")	Without Cover: 195 x 139 x 100 mm (7.68" x 5.47" x 3.94") With Cover: 195 x 139 x 153 mm (7.68" x 5.47" x 6.02")
OS	Windows 7 / 8 / 8.1 / 10	Windows 7 / 8 / 8.1 / 10	Windows 7 / 8 / 8.1 / 10	Windows 7 / 8 / 8.1 / 10	Windows 7 / 8 / 8.1 / 10
Hardware Requirements	Pentium® IV 2.4 GHz processor DVD-ROM Drive One available USB 2.0 Port 1GB RAM (2GB or higher recommended) 1GB free HDD space (2GB or larger recommended)	Pentium® IV 2.4 GHz processor DVD-ROM Drive One available USB 2.0 Port 1GB RAM (2GB or higher recommended) 1GB free HDD space (2GB or larger recommended)	Pentium® IV 2.4 GHz processor DVD-ROM Drive One available USB 2.0 Port 1GB RAM (2GB or higher recommended) 1GB free HDD space (2GB or larger recommended)	Pentium® IV 2.4 GHz processor DVD-ROM Drive One available USB 2.0 Port 1GB RAM (2GB or higher recommended) 1GB free HDD space (2GB or larger recommended)	Pentium® IV 2.4 GHz processor DVD-ROM Drive One available USB 2.0 Port 1GB RAM (2GB or higher recommended) 1GB free HDD space (2GB or larger recommended)